

HD-400 / HD-400R INDIRECT FIRED HEATER



INFORMATION SHEET

FEATURES

- **Versatile Fuel Options**
Natural gas or propane compatibility with dual fuel selector valve
- **Durable Heat Exchanger**
Fully Welded 16 ga 304 Stainless Steel
- **Robust Body Panels**
16 ga Carbon Steel with Chip-Resistant Coating
- **Reliable Mobility**
Flat-Free Tires with Reinforced Hubs
- **High-Quality Burner**
Equipped with Riello Burner



SPECIFICATIONS

	HD-400	HD-400R
BTUH	390,000 BTUH 114 kW	390,000 BTUH 114 kW
Air Movement	2,400 CFM 68 m ³ /min	3,500 CFM 99 m ³ /min
Weight	460 lbs 209 kg	480 lbs 218 kg
Dimensions	70" x 30" x 52" 178 x 76 x 132 cm	70" x 30" x 55" 178 x 76 x 140 cm
Power Supply	120 V / 15 A	120 V / 15 A
Current Draw	9 A	8 A
Ducting Capability	50' max 15 m max	100' max 30 m max
Recirculating	No	Up to 50' Up to 15 m
Certification	CSA	CSA
Fan Power	3/4 hp 0.55 kW	1 hp 0.74 kW
Thermostat	Yes	Yes
Fuel Consumption	LP: 18 lbs/hr, NG: 380 CFH LP: 8.2 kg/hr, NG: 10.8 m ³ /hr	LP: 18 lbs/hr, NG: 380 CFH LP: 8.2 kg/hr, NG: 10.8 m ³ /hr