

HO-TRAILBLAZER

INDIRECT FIRED PORTABLE TRAILER HEATER



INFORMATION SHEET

FEATURES

- 4 rooftop lifting lugs
- Fully welded body & 110% containment
- Storage duct/tool cabinet
- Easy access to start/control panel
- Heater rail system for easy heater serviceability
- LED work lights inside and out
- Electric emergency axel breakaway system
- 2" fuel fill inlet nozzle mount



SPECIFICATIONS



BTUH	2 x HO-400R heaters 390,000 BTUH (15 kW) / heater
Fans	1 hp 3,500 CFM / heater
Fuel Capacity	290 US Gal (1,100 L)
Fuel Consumption	Engine: 1.08 US Gal (4.09 L) / hr Heaters: 3 US Gal (11.36 L) / heater / hr
Run Time	Fully fuelled: 40 hrs
Engine	Kubota
Generator	8 kW Meccalte
Ducting Outlet	4 x 12" or 2 x 16"
Recirculating Inlet	2 x 16"
Dual axle	2 x 5,000 lbs
Dimensions	156" L x 89" W x 84" H (3.96 m x 2.26 m x 2.13 m)
Dry Weight	5,500 lbs (2,500 kg)
Certification	uETLc / CSA / UL